

**EC8001025**

**CABLE TIE PA 6.6 - 100x2,5 mm - TRANSLUCENT**

Conduits and fittings > Accessories and fittings > Fixings > Cable ties > Cable tie > Translucent



**Technical Symbols/Marks/Approvals**



**Norms**

EN 62275

**Description**

Cable tie made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Self-extinguishing grade V2 according to UL94 standard. High resistance to oils and mineral fats. Manufactured in compliance with EN 62275 and UL standards where applicable.

**Etim**

**GROUP EG000049 - Fasteners**

**CLASS EC000046 - Cable tie**

<b>Material</b>	Plastic	<b>Material quality</b>	Polyamide (PA)	<b>Halogen free</b>	Yes
<b>Surface protection</b>	Untreated	<b>Colour</b>	Colourless	<b>Transparent</b>	No
<b>Type of fastening</b>	None	<b>Model</b>	Internal toothing	<b>Band width</b>	2.5 mm
<b>Length belt/tape/tie</b>	100 mm	<b>Bundle diameter</b>	0-22 mm	<b>Min. tensile strength</b>	8.1 kg
<b>Operating temperature</b>	-40-85 °C	<b>Mounting temperature</b>	-5-60 °C	<b>Band closure</b>	Plastic lip/-cam
<b>UV-stable according to ASTM D6779</b>	No	<b>Fluorescent</b>	No	<b>Detectable</b>	No
<b>Text strip</b>	None	<b>Releasable closure</b>	No	<b>VG approval</b>	No
<b>MIL approval</b>	No	<b>UL approval</b>	No	<b>Inflammability class of insulation material according to UL94</b>	V2

## Barcode



8050880884049

**Pack**

100 NR

0.04 [kg]



8057711591732

**Cardboard**

5000 NR

0.205x0.385x0.15 [m]

2 [kg]