

EC8002036

CABLE TIE PA 6.6 - 200x3,6 mm - TRANSLUCENT

Conduits and fittings > Accessories and fittings > Fixings > Cable ties > Cable tie > Translucent



Technical Symbols/Marks/Approvals



Norms

EN 62275

Description

Cable tie made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Self-extinguishing grade V2 according to UL94 standard. High resistance to oils and mineral fats. Manufactured in compliance with EN 62275 and UL standards where applicable.

Etim

GROUP EG000049 - Fasteners

CLASS EC000046 - Cable tie

Material	Plastic	Material quality	Polyamide (PA)	Halogen free	Yes
Surface protection	Untreated	Colour	Colourless	Transparent	No
Type of fastening	None	Model	Internal toothing	Band width	3.6 mm
Length belt/tape/tie	200 mm	Bundle diameter	0-53 mm	Min. tensile strength	18.2 kg
Operating temperature	-40-85 °C	Mounting temperature	-5-60 °C	Band closure	Plastic lip/-cam
UV-stable according to ASTM D6779	No	Fluorescent	No	Detectable	No
Text strip	None	Releasable closure	No	VG approval	No
MIL approval	No	UL approval	No	Inflammability class of insulation material according to UL94	V2

Barcode



8050880884100

Pack

100 NR

0.11 [kg]



8057711591794

Cardboard

5000 NR

5.5 [kg]