elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC83036

BASE DIM.19x19 mm - MAx TIE WIDTH 3,6 mm TRANSPARENT

Conduits and fittings > Accessories and fittings > Fixings > Cable ties > Mounting base for cable ties > Adhesive backed mounting base - 4-ways

Technical Symbols/Marks/Approvals

UL94 V2 | CE | RoHS II | MADE IN PRC

Norms

EN 62275

Description

Two-way mounting base for cable ties made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Self-extinguishing grade V2 according to UL94 standard. High resistance to oils and mineral fats. Manufactured in compliance with EN 62275 and UL standards where applicable.

Etim

GROUP EG000049 - Fasteners

CLASS EC000449 - Mounting base and -element for cable ties

Material	Plastic	**Material quality**	Polyamide (PA)	**Colour**	Colourless
Type of fastening	Self-adhesive	**Width**	19 mm	**Length**	19 mm
Working temperature	-40-85 °C	**Suitable for cable tie width to**	3.6 mm		

Technical Characteristics

Tipologia	Base adesiva bidirezionale

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880884407

Pack

100 NR

0.09 [kg]

8057711592098

Cardboard

5000 NR

0.305x0.39x0.17 [m]

4.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.