
elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC890010

TERMINAL BLOCK SECTION 1,5 mmq - 10 BLOCKS PER BAR - PRICE PER BAR

Enclosures > Accessories > Accessories > Terminal blocks > Clamp terminal > Single-pole clamps - 10-piece slats

Technical Symbols/Marks/Approvals

GWT 960° | UL94 V2 | CE | RoHS II | MADE IN ITALY

Norms

EN 60670-1 EN 60670-24

Description

Insulated divisible single-pole terminal block. Terminal material: UNI EN 12167 CW 614N brass. Housing material: polycarbonate technopolymer. Self-extinguishing grade V0 according to UL94 standard. Resistance to abnormal heat (Glow Wire Test, IEC 60695-2-11 standard): up to 960°C. Rated voltage: 450V~. Maximum operating temperature +85°C. Manufactured in compliance with EN 60998-1, EN 60998-2-1 standards.
Nominal cross-section 1.5 mm²

Etim

GROUP EG000012 - Terminal blocks

CLASS EC001284 - Single- and multi-pole terminal strip

Number of poles	1	**Rated voltage**	450 V	**Mounting method**	Direct mounting
Connectable conductor cross section solid-core	1.5 ÷ 1.5 mm²	**Halogen free**	No	**Colour**	Other
Transparent	Yes	**Operating temperature**	0 ÷ 85 °C	**Inflammability class of insulation material according to UL94**	V0
Explosion-tested version 'Ex e'	No	**Rated current In**	18 A	**Type of electrical connection 1**	Screw connection
Material insulation body	Thermoplastic	**Closing plate required**	No		

Technical Characteristics

Tipologia	in stecche da 10 pezzi

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050880884513

Pack

10 NR

0.122 [kg]



8057711592203

Cardboard

900 NR

0.305x0.39x0.31 [m]

10.98 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.