

EC890015

**TERMINAL BLOCK SECTION 16 mmq -
10 BLOCKS PER BAR - PRICE PER
BAR**




IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Enclosures > Accessories > Accessories > Terminal blocks > Clamp terminal > Single-pole clamps - 10-piece slats

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Insulated divisible single-pole terminal block. Terminal material: UNI EN 12167 CW 614N brass. Housing material: polycarbonate technopolymer. Self-extinguishing grade V0 according to UL94 standard. Resistance to abnormal heat (Glow Wire Test, IEC 60695-2-11 standard): up to 960°C. Rated voltage: 450V~. Maximum operating temperature +85°C. Manufactured in compliance with EN 60998-1, EN 60998-2-1 standards.
Nominal cross-section 16.0 mm²

Etim

GROUP EG000012 - Terminal blocks

CLASS EC001284 - Single- and multi-pole terminal strip

Number of poles	1	Rated voltage	450 V	Mounting method	Direct mounting
Connectable conductor cross section solid-core	16-16 mm ²	Halogen free	No	Colour	Other
Transparent	Yes	Operating temperature	0-85 °C	Inflammability class of insulation material according to UL94	V0
Explosion-tested version 'Ex e'	No	Rated current In	76 A	Type of electrical connection 1	Screw connection
Material insulation body	Thermoplastic	Closing plate required	No		

Technical Characteristics

Tipologia in stecche da 10 pezzi

Barcode



8050880884568

Pack

10 NR

1.75 [kg]



8057711592258

Cardboard

100 NR

0.3x0.47x0.205 [m]

17.5 [kg]