

**EC890051**

**INSULATED BRASS TERMINAL BLOCK  
1X35 - 1X25 - 10X16 - BLUE**



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Enclosures > Accessories > Accessories > Terminal blocks > Terminals > Terminal blocks with support

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60670-1 EN 60670-24

**Description**

Insulated single-pole terminal block with DIN rail support. Terminal block material: UNI EN 12167 CW 614N brass. Housing material: nylon 6.6 technopolymer. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (Glow Wire Test, IEC 60695-2-11 standard): up to 960°C.

Rated voltage: 400VAC. Rated current 100A. Maximum operating temperature +60°C. Tightening torque 16-25 mm<sup>2</sup> = 2 N. Tightening torque 35 mm<sup>2</sup> = 3 N.

Blue color - Section 7x11 mm - 12 holes: 1x35 mm<sup>2</sup> - 1x25 mm<sup>2</sup> - 10x16 mm<sup>2</sup>.

**Etim**

**GROUP EG000015 - Energy distribution systems**

**CLASS EC000275 - Main line branch terminal**

<b>Number of poles</b>	1	<b>Mounting method</b>	DIN-rail/screw	<b>Width</b>	110 mm
<b>Height</b>	27.5 mm	<b>Depth</b>	13 mm	<b>Connection type</b>	Screwing
<b>Nominal current</b>	100 A	<b>Number of inputs</b>	1	<b>Number of outputs</b>	11
<b>Suitable for solid conductors</b>	Yes	<b>Suitable for stranded conductors</b>	Yes	<b>Conductor cross section, input</b>	35-35 mm <sup>2</sup>
<b>Conductor cross section, output</b>	16-25 mm	<b>Contact safe</b>	Yes		

## Barcode



8050880884605

**Pack**

10 NR

0.11x0.065x0.105 [m]

0.656 [kg]



8057711592296

**Cardboard**

320 NR

0.305x0.38x0.3 [m]

20.992 [kg]