

EC890057



**INSULATED BRASS TERMINAL BLOCK
1X35 - 1X25 - 10X16 - BLACK**

Enclosures > Accessories > Accessories > Terminal blocks > Terminals > Terminal blocks with support



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Insulated single-pole terminal block with DIN rail support. Terminal block material: UNI EN 12167 CW 614N brass. Housing material: nylon 6.6 technopolymer. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (Glow Wire Test, IEC 60695-2-11 standard): up to 960°C.

Rated voltage: 400VAC. Rated current 100A. Maximum operating temperature +60°C. Tightening torque 16-25 mm² = 2 N. Tightening torque 35 mm² = 3 N.

Black color - Section 7x11 mm - 12 holes: 1x35 mm² - 1x25 mm² - 10x16 mm².

Etim

GROUP EG000015 - Energy distribution systems

CLASS EC000275 - Main line branch terminal

| | | | | | |
|--|----------|---|----------------|---------------------------------------|-----------------------|
| Number of poles | 1 | Mounting method | DIN-rail/screw | Width | 110 mm |
| Height | 27.5 mm | Depth | 13 mm | Connection type | Screwing |
| Nominal current | 100 A | Number of inputs | 1 | Number of outputs | 11 |
| Suitable for solid conductors | Yes | Suitable for stranded conductors | Yes | Conductor cross section, input | 35-35 mm ² |
| Conductor cross section, output | 16-25 mm | Contact safe | Yes | | |

Barcode



8050880884667

Pack

10 NR

0.11x0.065x0.105 [m]

0.656 [kg]



8057711592357

Cardboard

320 NR

0.3x0.395x0.3 [m]

20.992 [kg]