

EC890057



**INSULATED BRASS TERMINAL BLOCK
1X35 - 1X25 - 10X16 - BLACK**

Enclosures > Accessories > Accessories > Terminal blocks > Terminals > Terminal blocks with support



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 60670-1 EN 60670-24

Description

Insulated single-pole terminal block with DIN rail support. Terminal block material: UNI EN 12167 CW 614N brass. Housing material: nylon 6.6 technopolymer. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (Glow Wire Test, IEC 60695-2-11 standard): up to 960°C.

Rated voltage: 400VAC. Rated current 100A. Maximum operating temperature +60°C. Tightening torque 16-25 mm² = 2 N. Tightening torque 35 mm² = 3 N.

Black color - Section 7x11 mm - 12 holes: 1x35 mm² - 1x25 mm² - 10x16 mm².

Etim

GROUP EG000015 - Energy distribution systems

CLASS EC000275 - Main line branch terminal

Number of poles	1	Mounting method	DIN-rail/screw	Width	110 mm
Height	27.5 mm	Depth	13 mm	Connection type	Screwing
Nominal current	100 A	Number of inputs	1	Number of outputs	11
Suitable for solid conductors	Yes	Suitable for stranded conductors	Yes	Conductor cross section, input	35-35 mm ²
Conductor cross section, output	16-25 mm	Contact safe	Yes		

Barcode



8050880884667

Pack

10 NR

0.11x0.065x0.105 [m]

0.656 [kg]



8057711592357

Cardboard

320 NR

0.3x0.395x0.3 [m]

20.992 [kg]