EC990GFE16

WHITE SPIRAL CONDUIT INT. DIAM. 16 mm

Canalizaciones > ClimatizaciÓn > Canales para aire acondicionado > Tubo de descarga y soporte > Tubo espiral para descarga de condensación

Technical Symbols/Marks/Approvals

IP40 | CE | RoHS II | MADE IN ITALY

Estándares

CLASS. 1111

Descripción

Tubo spiral flexible fabricado en PVC autoextinguible. Para instalaciones de desagüe de condensados.

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	**Halogen free**	No	**Colour**	White
UV resistant	Sí	**Working temperature**	-25-70 °C	**Nominal diameter**	16 mm
Inner diameter	16 mm	**Outer diameter**	20.2 mm	**Compressive strength**	125 N
Bending radius, static	160 mm	**Sheathing material**	Other	**Material filament**	Helix of rigid plastic
Plain interior	Sí	**Plain exterior**	No	**Flexibility**	Flexible

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880885329
Cardboard
30 MT
0.38x0.38x0.11 [m]
2.499 [kg]

8057711592531
Pallet
5400 MT
0.8x1.2x2.4 [m]
449.82 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.