elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

ECAE6017B

EXTERNAL ANGLE DIM. 60X17 WHITE

Canalizaciones > Pared y techo > Minicanales > Serie mc-mca-ma - accesorios > Ángulo exterior para minicanales

Technical Symbols/Marks/Approvals

IP40 | IK07 | GWT 650° | CE | RoHS II | MADE IN ITALY

Estándares

EN 50085-1 EN50085-2-1

Descripción

Ángulo externo para cambio de dirección a 90°. Enganche por clic en el minicanal.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000872 - Outer corner for wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Sí	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK07	**Width**	60 mm
Depth	17 mm	**Model**	Moulded hood	**RAL-number**	9001
Mounting method cover	Spanned	**With protective foil**	No	**Working temperature**	-5-60 °C
With cable fixing clip	No	**With duct connector**	Sí	**Bottom perforation**	No
Angle	90-90 °	**Number of covers**	1	**Cover width 1**	60 mm
Cover width 2	0 mm	**Cover width 3**	0 mm	**Symmetric**	Sí

Documentation available for download

Certification

Canali e Minic Serie MC-CP.pdf

Certification

LICENCE 669941_CP-MC.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880885787
Pack
2 NR
0.052 [kg]

8057711592685
Cardboard
50 NR
0.39x0.295x0.15 [m]
1.3 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.