elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECGFLEX32

COUPLING FOR PLIABLE CONDUIT IP40 32 mm - TRANSLUCENT

Tuberías y accesorios > Accesorios de tubería > Uniones y sistemas de fijaciÓn > Accesorios ip40-64 > manguito para tubos corrugados > Union para tubos corrugados

Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | NF | MADE IN ITALY

Estándares

EN 61386-1 EN 61386-22

Descripción

Acoplamiento para tubo corrugado de polietileno libre de halógenos. Resistencia al calor anormal (GWT, norma IEC 60695-2-11): hasta 650°C. Grado de protección: IP40. Resistencia de aislamiento > 100 MΩ. Temperaturas durante la instalación: mínima -5°C, máxima +90°C.
Referencias normativas: EN 61386-1, EN 61386-22.
Diámetro interno nominal 32 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001492 - Coupler for cable protection tube for underground application

Material	Plastic	**Material quality**	Polyethylene (PE)	**Halogen free**	Sí
Surface protection	Untreated	**Colour**	Colourless	**UV resistant**	No
Surface polished	No	**Separable**	No	**Inner diameter**	31.7 mm
Outer diameter	35.5 mm	**Nominal diameter, connection 1**	32 mm	**Nominal diameter, connection 2**	32 mm
Reducing	No	**With rubber seal**	No		

Technical Characteristics

largura	60 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

LICENCE - ICTA - 2022 - Licence - Certificat Produits-14693487-778130-0000732967-9.p....pdf

Barcode

8050880888665

Pack

50 NR

0.69 [kg]

8057711593989

Cardboard

400 NR

0.605x0.4x0.26 [m]

5.52 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.