elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECMC6017B

MINITRUNKING FRONT-HOOKING LID 60X17 WHITE 3 COMPARTMENTS

Canalizaciones > Pared y techo > Minicanales > Serie mc - con tapa frontal > Minicanales > Blanco

Technical Symbols/Marks/Approvals

IP40 | IK07 | UL94 V0 | GWT 960° | CE | RoHS II | NF | MADE IN ITALY

Estándares

EN 50085-1 EN 50085-2-1

Descripción

Minicanal fabricado en tecnopolímero a base de PVC rígido autoextinguible. Pretaladrado del fondo para fijación con tornillos y tacos. Fondo diseñado para fijación rápida con adhesivos de silicona. Tapa de enganche frontal suministrada montada.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000059 - Mini/maxi trunking

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Polyvinyl chloride (PVC)
Halogen free	No	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Transparent**	No	**Impact strength**	IK07
Type of fastening	Bottom perforation	**Width**	60 mm	**Height**	17 mm
Length	2000 mm	**Usable cross section**	685 mm²	**RAL-number**	9001
With protective foil	No	**Working temperature**	-5 ÷ 60 °C	**Cover model**	Loose
Suitable for circuit integrity	No	**Number of permanent partitions**	2	**Number of plug-in partitions**	0
With cable fixing clip	No	**With duct connector**	No	**Delivery on roll**	No
Pre-stamping	No				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Instruction booklet

Istruzioni minicanali.pdf



Certification

Canali e Minic Serie MC-CP.pdf



Certification

LICENCE 669941_CP-MC.pdf

Barcode

8054320287025

Cardboard

70 MT

0.248x0.143x2.03 [m]

24.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.