

ECPA08

SELF-EXTINGUISHING SPIRAL WRAP 8X10 WHITE



Canalizaciones > Cableado > Canales de cuadro > Espiral >
Tubo espiral para cables > Blanco - autoextinguible



Technical Symbols/Marks/Approvals

UL94
V2

CE

RoHS II

MADE
IN
ITALY

Estándares

UL94

Descripción

Polyethylen spiral wrap. To be used in the electrical cabinets. For use in wiring or surface-mounted panels. Can be used to collect and route connection cables.

Etim

GROUP EG000003 - Protective hose systems

CLASS EC002604 - Cable bundle hose

Material	Plastic	Material quality	Polyethylene fibreglass-reinforced	Halogen free	No
Colour	White	Transparent	No	Model	Spiral hose
UV resistant	No	Bundle diameter	340-340 mm	Operating temperature	-5-60 °C
Nominal diameter	10 mm	Operating temperature, short-run	60 °C	Fire resistant properties	According to UL 94 V2
Wall thickness	0.75 mm	Filament width	10 mm		

Technical Characteristics

Díámetro exterior	10 mm	perforar	8 mm
--------------------------	-------	-----------------	------

Barcode



8054320286813

Pack

25 MT

1.1875 [kg]



8057711597277

Cardboard

200 MT

0.36x0.465x0.23 [m]

9.5 [kg]