elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET




IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

ECS6060

SLOTTED TRUNKING WITH COVER S 4/6/4 DIM. 60X60

Canalizaciones > Cableado > Canales de cuadro > Canaletas ranuradas > Sistemas de canales ranurados > Gris - tipo s - ranuras estrechas 4/6/4

Technical Symbols/Marks/Approvals

UL94 V0 | GWT 960° | CE | RoHS II | | | RINA | MADE IN ITALY

Estándares

EN 50085-1 EN 50085-2-3 UL 1565

Descripción

Canaleta de cableado de tecnopolímero a base de PVC autoextinguible UL94 - V0. Fondo troquelado según las normas DIN 43659. Doble línea de rotura para una fácil y rápida extracción de la lengüeta y de toda la pared de la canaleta (con herramienta).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	**Halogen free**	No	**Colour**	Grey
Type of fastening	Bottom perforation	**Width**	60 mm	**Height**	60 mm
Length	2000 mm	**Diameter**	0 mm	**Distance of slots**	6 mm
Slit width	4 mm	**Type of side wall**	Hole-/slot punching	**Self-extinguishing**	Sí
Flexible	No	**Usable cross section**	3046 mm²	**With cover/lid**	Sí
RAL-number	7030				

Technical Characteristics

Predisposición del separador	NO

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Certificato UL A-S ATL AMF E331386.pdf



Certification

RINA DCMTVL_1005538_380865962_2025.PDF



Certification

Canali asolati tipo S IMQ_EI617_2020.pdf

Barcode

8054320286394

Cardboard

32 MT

0.26x0.18x2.027 [m]

22 [kg]

8054320280606

Pallet

576 MT

396 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.