



## ECSE8040V

Residencial > Mecanismos > FÁCil > Dispositivos fáciles > Enchufe



### Technical Symbols/Marks/Approvals



## Etim

### GROUP EG000013 - Domestic switching devices

### CLASS EC000125 - Socket outlet

<b>Mounting method</b>	Flush-mounted	<b>Number of units</b>	1	<b>Label space/information surface</b>	Si
<b>Material</b>	Plastic	<b>Material quality</b>	Thermoplastic	<b>Halogen free</b>	No
<b>Anti-bacterial treatment</b>	No	<b>Surface protection</b>	Untreated	<b>Surface finishing</b>	Glossy
<b>Colour</b>	Green	<b>Transparent</b>	No	<b>With hinged lid</b>	No
<b>Imprint/indication</b>	None	<b>Suitable for degree of protection (IP)</b>	IP20	<b>Number of modules (module system)</b>	2
<b>Device width</b>	48 mm	<b>Device height</b>	49 mm	<b>Device depth</b>	46 mm
<b>Min. depth of built-in installation box</b>	46 mm	<b>Nominal voltage</b>	250 V	<b>Number of socket outlets switchable</b>	0
<b>With enhanced contact protection</b>	No	<b>Metallic colour</b>	No	<b>Lockable</b>	No
<b>Eject-mechanism</b>	No	<b>Insulated mounting</b>	No	<b>With function lighting</b>	No
<b>Overvoltage protection</b>	No	<b>Fault current protection</b>	No	<b>With loop through function</b>	No
<b>With on/off switch</b>	No	<b>Rotated central insert</b>	No	<b>Nominal current</b>	16 A
<b>With built-in bluetooth speaker</b>	No				

## Documentation available for download



## Barcode



8050507870172

**Unit**

1 NR

0.0542 [kg]



8054320289142

**Pack**

6 NR

0.19x0.1x0.05 [m]

0.3252 [kg]



8056351668644

**Cardboard**

120 NR

0.215x0.4x0.31 [m]

6.504 [kg]