elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECSH10080

HALOGEN FREE SLOTTED TRUNKING WITH COVER 4/6/4 DIM. 100X80

Canalizaciones > Cableado > Canales de cuadro > Canaletas ranuradas libres de halÓgenos > Sistemas de canales ranurados > Gris claro - tipo s - ranuras estrechas 4/6/4

Technical Symbols/Marks/Approvals

HF | UL94 V2 | GWT 960° | -25° | +90° | CE | RoHS II | MADE IN ITALY

Estándares

EN 50267-2-1 EN 50267-2-2 IEC 60754-1 IEC 60754-2 EN 50085-1

EN 50085-2-3 UL 1565

Descripción

Canaleta de cableado fabricada en tecnopolímero libre de halógenos. Autoextinguible según las normas UL94 - V2 a 1,6 mm. Resistencia al calor anormal: hasta 960°C (GWT). Estabilidad dimensional comprendida entre -25°C y +90°C. Fondo troquelado según las normas DIN 43659. Doble línea de rotura para una fácil y rápida extracción de la lengüeta y de toda la pared de la canaleta (con herramienta)

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Other	**Halogen free**	Sí	**Colour**	Grey
Type of fastening	Bottom perforation	**Width**	100 mm	**Height**	80 mm
Length	2000 mm	**Diameter**	0 mm	**Distance of slots**	6 mm
Slit width	4 mm	**Type of side wall**	Hole-/slot punching	**Self-extinguishing**	Sí
Flexible	No	**Usable cross section**	7156 mm²	**With cover/lid**	Sí
RAL-number	7035				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Canali tipo SH-AH - Analysis Test Report.pdf

Barcode

8054320286295

Cardboard

24 MT

0.26x0.26x2.03 [m]

15.4992 [kg]

8055035960517

Pallet

288 MT

1.2x0.8x2.2 [m]

185.9904 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.