

ECTC1225

PLIABLE PVC CONDUIT 22212 Ø25 mm - 50 m



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados
(mangueras) > Serie tc12 - pvc - 22212 - 320 n > Tubo plástico
para instalación eléctrica > Gris claro

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22


Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	Sí	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	18.8 mm
Outer diameter	25 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Barcode




8054320285892

Cardboard

50 MT

0.6x0.6x0.17 [m]

3.17 [kg]



8057711597727

Pallet

2800 MT

0.8x1.2x2.5 [m]

177.52 [kg]