

ECTC1240T

PLIABLE PVC CONDUIT 22212 Ø40 mm - 25 m WITH DRAW TAPE



IMMAGINE
RAPPRESENTATIVA

EC REPRESENTATIVE
IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados
(mangueras) > Serie tc12 - pvc - 22212 - 320 n > Tubo plástico
para instalación eléctrica > Gris claro - con guía pasacables

Technical Symbols/Marks/Approvals

UL94 V0	GWT 960°	CE	RoHS II	OVE	MADE IN ITALY
------------	-------------	----	---------	-----	---------------------

Estándares

EN 61386-1 EN 61386-22


Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Light (class 2 / 1 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	Sí	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	31.5 mm
Outer diameter	40 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Barcode



8054320285823

Cardboard

25 MT

0.6x0.6x0.22 [m]

3.375 [kg]



8057711597796

Pallet

1000 MT

0.8x1.2x2.5 [m]

135 [kg]