

**ECTC182010**



**PLIABLE PVC CONDUIT 33412 Ø20 mm  
- 10 m**



Tuberías y accesorios > Tubería > Tubos corrugados (mangueras) > Serie tc18 - pvc -25°C - 33412 - 750 n > Tubo plástico para instalación eléctrica > Gris - rollos de 10 metros

**Technical Symbols/Marks/Approvals**



**Estándares**

EN 61386-1 EN 61386-22

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Sí	<b>Material</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Colour</b>	Grey	<b>RAL-number</b>	7031	<b>UV resistant</b>	No
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-25-60 °C	<b>Bending strength</b>	Pliable
<b>Compressive strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>Impact strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>With sleeve</b>	No
<b>Fire retardant version</b>	Sí	<b>Surface mounting</b>	No	<b>Suitable for installation on wood</b>	No
<b>Suitable for hollow wall installation</b>	No	<b>Suitable for concrete installation</b>	Sí	<b>Machine and systems installation</b>	No
<b>Suitable for underfloor installation (screed)</b>	No	<b>Suitable for outdoor installation</b>	No	<b>Inner diameter</b>	13.4 mm
<b>Outer diameter</b>	20 mm	<b>High conducting inner coating</b>	No	<b>With metre indication</b>	No

**Documentation available for download**

**Certification**  
OVE\_50017-002-09.pdf

**Certification**  
OVE\_50017-002-10.pdf

## Barcode

 barcode

8032793879466

**Unit**

1 NR

0.6994 [kg]



8033576778952

**Pallet**

216 NR

151.0704 [kg]