

ECTC182025

PLIABLE PVC CONDUIT 33412 Ø20 mm - 25 m



Tuberías y accesorios > Tubería > Tubos corrugados
(mangueras) > Serie tc18 - pvc -25°C - 33412 - 750 n > Tubo
plástico para instalación eléctrica > Gris - rollos de 25 metros

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22


Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7031	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	Sí	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	13.4 mm
Outer diameter	20 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Barcode



8032793879435

Unit

1 NR

1.699 [kg]



8033576778853

Pallet

121 NR

205.579 [kg]