

ECTC1840



**PLIABLE PVC CONDUIT 33412 Ø40 mm
- 25 m**



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados (mangueras) > Serie tc18 - pvc -25°c - 33412 - 750 n > Tubo plástico para instalación eléctrica > Gris

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

| | | | | | |
|--|---------|--|--------------------------|---|---------|
| Flush-mounted installation | Sí | Material | Polyvinyl chloride (PVC) | Halogen free | No |
| Colour | Grey | RAL-number | 7031 | UV resistant | No |
| Suitable for underground installation | No | Operating temperature | -25-60 °C | Bending strength | Pliable |
| With sleeve | No | Fire retardant version | Sí | Surface mounting | No |
| Suitable for installation on wood | No | Suitable for hollow wall installation | No | Suitable for concrete installation | Sí |
| Machine and systems installation | No | Suitable for underfloor installation (screed) | No | Suitable for outdoor installation | No |
| Inner diameter | 31.2 mm | Outer diameter | 40 mm | High conducting inner coating | No |
| With metre indication | No | | | | |

Documentation available for download

Certification

OVE_50017-002-09.pdf

Certification

OVE_50017-002-10.pdf

Barcode




8054320285250

Cardboard

25 MT

5.125 [kg]



BAHAGTC1840

Pallet

1000 MT

205 [kg]