

**ECTG1232-2**



**RIGID CONDUIT 22211 Ø32 mm - 2 m**

Tuberías y accesorios > Tubería > Tubos rígidos > Serie tg12 - pvc - 22211 - 320 n > Tubo plástico para instalación eléctrica > Barra de 2 metros



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**



**Estándares**

EN 61386-1 EN 61386-21

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Sí	<b>Material</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Colour</b>	Grey	<b>RAL-number</b>	7035	<b>UV resistant</b>	Sí
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-5-60 °C	<b>Bending strength</b>	Rigid
<b>Compressive strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>Impact strength class according to EN 61386-1</b>	Light (class 2 / 1 Joule)	<b>With sleeve</b>	No
<b>Fire retardant version</b>	Sí	<b>Surface mounting</b>	Sí	<b>Suitable for installation on wood</b>	Sí
<b>Suitable for hollow wall installation</b>	Sí	<b>Suitable for concrete installation</b>	No	<b>Machine and systems installation</b>	No
<b>Suitable for underfloor installation (screed)</b>	No	<b>Suitable for outdoor installation</b>	No	<b>Inner diameter</b>	29.1 mm
<b>Outer diameter</b>	32 mm	<b>High conducting inner coating</b>	No	<b>With metre indication</b>	No

## Barcode



8054320284994

### Cardboard

20 MT

4.256 [kg]

 barcode

8057711598625

### Pallet

560 MT

2x0.61x0.62 [m]

119.168 [kg]