

**ECTG1250-2**

**RIGID CONDUIT 22211 Ø50 mm - 2 m - BUNDLE 10**



Tuberías y accesorios > Tubería > Tubos rígidos > Serie tg12 - pvc - 22211 - 320 n > Tubo plástico para instalación eléctrica > Barra de 2 metros



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**



**Estándares**

EN 61386-1 EN 61386-21

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

|   |                           |  |                           |  |         |
|---|---------------------------|--|---------------------------|--|---------|
| <b>Flush-mounted installation</b>                         | Sí                        | <b>Material</b>                                      | Polyvinyl chloride (PVC)  | <b>Halogen free</b>                      | No      |
| <b>Colour</b>   | Grey                      | <b>RAL-number</b>                                    | 7035                      | <b>UV resistant</b>                      | Sí      |
| <b>Suitable for underground installation</b>              | No                        | <b>Operating temperature</b>                         | -5-60 °C                  | <b>Bending strength</b>                  | Rigid   |
| <b>Compressive strength class according to EN 61386-1</b> | Light (class 2 / 1 Joule) | <b>Impact strength class according to EN 61386-1</b> | Light (class 2 / 1 Joule) | <b>With sleeve</b>                       | No      |
| <b>Fire retardant version</b>                             | Sí                        | <b>Surface mounting</b>                              | Sí                        | <b>Suitable for installation on wood</b> | Sí      |
| <b>Suitable for hollow wall installation</b>              | Sí                        | <b>Suitable for concrete installation</b>            | No                        | <b>Machine and systems installation</b>  | No      |
| <b>Suitable for underfloor installation (screed)</b>      | No                        | <b>Suitable for outdoor installation</b>             | No                        | <b>Inner diameter</b>                    | 46.4 mm |
| <b>Outer diameter</b>                                     | 50 mm                     | <b>High conducting inner coating</b>                 | No                        | <b>With metre indication</b>             | No      |

## Barcode




8054320284918

### Cardboard

10 MT

3.955 [kg]



8057711598700

### Pallet

240 MT

94.92 [kg]