

ECICTA32GC

HF ICTA PLIABLE PP CONDUIT 34223
Ø32 mm - 50 m - LIGHT GREY - RAL
7035



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados
(mangueras) > Serie icta - pp - 34223 - 750 n > Tubo plástico
para instalación eléctrica > Negro

Technical Symbols/Marks/Approvals

HF	GWT 850°	+90°		CE	RoHS II	MADE IN ITALY
----	-------------	------	--	----	---------	---------------------

Estándares

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polypropylene (PP)	Halogen free	Sí
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	No	Suitable for installation on wood	Sí
Suitable for hollow wall installation	Sí	Suitable for concrete installation	Sí	Machine and systems installation	No
Suitable for underfloor installation (screed)	Sí	Suitable for outdoor installation	No	Inner diameter	24.4 mm
Outer diameter	32 mm	High conducting inner coating	Sí	With metre indication	No

Documentation available for download

Certification

Test Report ICTA
Contenuto alogeni
MI23-0092109-01.pdf

Brochure

BROCHURE TUBI
doppie.pdf

Barcode



8056351668316

Cardboard

50 MT

0.55x0.55x0.27 [m]

6.415 [kg]



8056351668378

Pallet

1800 MT

0.8x1.2x2.5 [m]

230.94 [kg]