

ECS2580B



SLOTTED TRUNKING WITH COVER S 4/6/4 DIM. 25X80 WHITE

Canalizaciones > Cableado > Canales de cuadro > Canaletas ranuradas > Sistemas de canales ranurados > Blanco - tipo s - ranuras estrechas 4/6/4




IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Technical Symbols/Marks/Approvals



Estándares

EN 50085-1 EN 50085-2-3 UL 1565

Descripción

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	White
Type of fastening	Bottom perforation	Width	25 mm	Height	80 mm
Length	2 m	Distance of slots	6 mm	Slit width	4 mm
Type of side wall	Hole-/slot punching	Self-extinguishing	Sí	Flexible	No
Usable cross section	1520 mm ²	With cover	Sí	RAL-number	9001

Technical Characteristics

Predisposición del separador NO

Documentation available for download



Certification

Certificato UL A-S
ATL AMF
E331386.pdf



Certification

RINA
DCMTVL_1005538
_380865962_2025.
PDF



Certification

Canali asolati tipo S
IMQ_EI617_2020.p
df

Barcode



8059307211680

Cardboard

56 MT

0.26x0.18x2.027 [m]

24.0016 [kg]



8055035960265

Pallet

1008 MT

1.2x0.8x2.2 [m]

432.0288 [kg]