

ECTC122525T



**PLIABLE PVC CONDUIT 22212 Ø25 mm
- 25 m WITH DRAW TAPE**

Tuberías y accesorios > Tubería > Tubos corrugados (mangueras) > Serie tc12 - pvc - 22212 - 320 n > Tubo plástico para instalación eléctrica > Gris claro - con guía pasacables - rollos de 25 metros



IMMAGINE RAPPRESENTATIVA / REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

| | | | | | |
|---|---------------------------|--|---------------------------|--|---------|
| Flush-mounted installation | Sí | Material | Polyvinyl chloride (PVC) | Halogen free | No |
| Colour | Grey | RAL-number | 7035 | UV resistant | No |
| Suitable for underground installation | No | Operating temperature | -5-60 °C | Bending strength | Pliable |
| Compressive strength class according to EN 61386-1 | Light (class 2 / 1 Joule) | Impact strength class according to EN 61386-1 | Light (class 2 / 1 Joule) | With sleeve | No |
| Fire retardant version | Sí | Surface mounting | No | Suitable for installation on wood | No |
| Suitable for hollow wall installation | No | Suitable for concrete installation | Sí | Machine and systems installation | No |
| Suitable for underfloor installation (screed) | No | Suitable for outdoor installation | No | Inner diameter | 18.8 mm |
| Outer diameter | 25 mm | High conducting inner coating | No | With metre indication | No |

Documentation available for download

Certification
OVE-CERTIFICATE
OVE_50017-001-09.pdf

Certification
OVE-CERTIFICATE
OVE_50017-001-10.pdf

Barcode



8054382041252

Unit

1 NR

0.35x0.35x0.27 [m]

1.7167 [kg]



8054320280507

Pallet

90 NR

154.503 [kg]