

ECTC1816T



**PLIABLE PVC CONDUIT 33412 Ø16 mm
- 100 m WITH DRAW TAPE**

Tuberías y accesorios > Tubería > Tubos corrugados (mangueras) > Serie tc18 - pvc -25°c - 33412 - 750 n > Tubo plástico para instalación eléctrica > Gris - con guía pasacables



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7031	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-60 °C	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	Sí	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	10.2 mm
Outer diameter	16 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download

Certification
OVE_50017-002-09.pdf

Certification
OVE_50017-002-10.pdf

Barcode



8054320281870

Cardboard

100 MT

5.11 [kg]



8054320280958

Pallet

6000 MT

306.6 [kg]