

ECTC1850T

PLIABLE PVC CONDUIT 33412 Ø50 mm - 25 m WITH DRAW TAPE



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados
(mangueras) > Serie tc18 - pvc -25°c - 33412 - 750 n > Tubo
plástico para instalación eléctrica > Gris - con guía pasacables

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Grey	RAL-number	7031	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-60 °C	Bending strength	Pliable
With sleeve	No	Fire retardant version	Sí	Surface mounting	No
Suitable for installation on wood	No	Suitable for hollow wall installation	No	Suitable for concrete installation	Sí
Machine and systems installation	No	Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No
Inner diameter	39.2 mm	Outer diameter	50 mm	High conducting inner coating	No
With metre indication	No				

Documentation available for download



Barcode



8054320282785

Cardboard

25 MT

7.97 [kg]



8054320283126

Pallet

800 MT

255.04 [kg]