EC350C7P

FLUSH MOUNTING JUNCTION BOX WITH COVER AND PROTECTION LID DIM. 294X152X70

Envolvientes > Empotrable > Cajas de empalme > Serie 350 - para paredes murales > Caja para montaje empotrado en pared > Fondo naranja - con protector de mortero

Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | MADE IN ITALY

Estándares

EN 60670-1 EN 60670-22

Descripción

Caja de derivación empotrable para paredes de mampostería. Fabricada en tecnopolímero antichoque libre de halógenos. Completa con tapa y tornillos de fijación. Tapa gofrada pintable. Con cubremortero de cartón. Resistencia al calor anormal hasta 650° C (GWT). Fabricada de conformidad con las normas EN 60670-1:2005 y EN 60670-22:2006. Temperaturas durante la instalación: mínima –15°C, máxima +60°C. Grado de protección IP40.
Dimensiones: 294x152x70 mm
Preparada para 3 compartimentos

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

Max. conductor cross section	0	**Mounting method**	Flush-mounted	**Degree of protection (IP)**	IP40
Material	Plastic	**Halogen free**	Sí	**Surface protection**	Untreated
Colour	Orange	**Width**	295 mm	**Model**	Other
Length	152 mm	**Diameter**	0 mm	**Cover model**	Blind cover
Inner depth	69 mm	**Circuit integrity**	None	**Equipped with**	None
Shape	Rectangular	**Number of inlets**	26	**Inlet from the rear**	Sí
Compliant with BS 4662	No	**Couplable**	No	**Transparent cover**	No
Pipe locking	No	**Construction type**	Cable junction box	**Airtight**	No
For tube diameter	Other	**Cover attachment**	Screwed	**Sealable**	No
With screening	No	**Provided with revolving ring**	No	**Depth**	0-69 mm
For number of device inserts	0	**Mounting switching equipment**	Screwing	**With screws**	Sí
Housing feed-through by break-out opening	Sí	**Housing feed-through by seal membrane**	No	**Housing feed-through by nozzle**	No
Housing feed-through by step membrane	No	**Pipe locking optional**	No	**Number of included spouts**	0
Number of poles of the clamp	0	**Clamp position fixed**	No	**Luminaire hook mounting**	No
Nozzle	None	**Special application**	None	**With partition panel**	No

Technical Characteristics

Preparación para compartimentos/carriles DIN	3

Documentation available for download

Certification

Serie 350 IMQ_CA02.01670_2018.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8032793872887
Unit
1 NR
0.4114 [kg]

8059307213301
Cardboard
28 NR
0.605x0.405x0.55 [m]
11.5192 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.