

EC350C9P

FLUSH MOUNTING JUNCTION BOX WITH COVER AND PROTECTION LID DIM. 480X160X70



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Envoltorios > Empotrable > Cajas de empalme > Serie 350 -
para paredes murales > Caja para montaje empotrado en
pared > Fondo naranja - con protector de mortero

Technical Symbols/Marks/Approvals

IP40	HF	GWT 650°	CE	RoHS II		MADE IN ITALY
------	----	-------------	----	---------	--	---------------------

Estándares

EN 60670-1 EN 60670-22

Descripción

Caja de derivación empotrable para paredes de mampostería. Fabricada en tecnopolímero antichoque libre de halógenos. Completa con tapa y tornillos de fijación. Tapa gofrada pintable. Con cubremortero de cartón. Resistencia al calor anormal hasta 650° C (GWT). Fabricada de conformidad con las normas EN 60670-1:2005 y EN 60670-22:2006. Temperaturas durante la instalación: mínima -15°C, máxima +60°C. Grado de protección IP40. Dimensiones: 480x160x70 mm. Preparada para 3 compartimentos.

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002601 - Box/housing for built-in mounting in the wall/ceiling

Max. conductor cross section	0	Mounting method	Flush-mounted	Degree of protection (IP)	IP40
Material	Plastic	Halogen free	Sì	Surface protection	Untreated
Colour	Orange	Width	480 mm	Model	Other
Length	160 mm	Diameter	0 mm	Cover model	Blind cover
Inner depth	69 mm	Circuit integrity	None	Equipped with	None
Shape	Rectangular	Number of inlets	48	Inlet from the rear	Sì
Compliant with BS 4662	No	Couplable	No	Transparent cover	No
Pipe locking	No	Construction type	Cable junction box	Airtight	No
For tube diameter	Other	Cover attachment	Screwed	Sealable	No
With screening	No	Provided with revolving ring	No	Depth	0-69 mm
For number of device inserts	0	Mounting switching equipment	Screwing	With screws	Sì
Housing feed-through by break-out opening	Sì	Housing feed-through by seal membrane	No	Housing feed-through by nozzle	No
Housing feed-through by step membrane	No	Pipe locking optional	No	Number of included spouts	0
Number of poles of the clamp	0	Clamp position fixed	No	Luminaire hook mounting	No
Nozzle	None	Special application	None	With partition panel	No

Technical Characteristics

Preparación para compartimentos/carriles DIN 3

Documentation available for download



Barcode



8032793872900

Unit

1 NR

0.6667 [kg]



8059307213325

Cardboard

18 NR

0.605x0.405x0.55 [m]

12.0006 [kg]