

ECTC152575T

PLIABLE PVC CONDUIT 33212 Ø25 mm - 75 m WITH DRAW TAPE



IMMAGINE
RAPPRESENTATIVA

REPRESENTATIVE
IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados
(mangueras) > Serie tc15 - pvc - 33212 - 750 n > Tubo plástico
para instalación eléctrica > Negro - con guía pasacables

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22



Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polyvinyl chloride (PVC)	Halogen free	No
Colour	Black	RAL-number	9005	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-60	Bending strength	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	No	Suitable for installation on wood	No
Suitable for hollow wall installation	No	Suitable for concrete installation	Sí	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	17.7 mm
Outer diameter	25 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Barcode



8055035966106

Cardboard

75 MT

5.85 [kg]



8033576772158

Pallet

3300 MT

257.4 [kg]