

ECTP2025T

HF PAIBLE PP CONDUIT 23323 Ø25 mm - 50 m - WITH DRAW TAPE - BLACK



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados (mangueras) > Serie tp20 - pp - 23323 - 750 n > Tubo plástico para instalación eléctrica > Negro - con guía pasacables

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polypropylene (PP)	Halogen free	Sí
Colour	Black	RAL-number	9005	UV resistant	No
Suitable for underground installation	No	Operating temperature	-15-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Light (class 2 / 1 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	Sí	Suitable for installation on wood	Sí
Suitable for hollow wall installation	Sí	Suitable for concrete installation	No	Machine and systems installation	No
Suitable for underfloor installation (screed)	No	Suitable for outdoor installation	No	Inner diameter	18.5 mm
Outer diameter	25 mm	High conducting inner coating	Sí	With metre indication	No

Barcode



8055035963587

Cardboard

50 MT

3.47 [kg]



8055035963594

Pallet

3000 MT

208.2 [kg]