

EC440C5

SMOOTH SIDED BOX IP56 WITH TRANSPARENT LID DIM. 150X110X140



Envoltorios > Montaje en pared > Cajas estancas > Serie 440
- paredes lisas - tapa alta transparente > Caja estanca para
montaje en pared

Technical Symbols/Marks/Approvals

IP56	IK08	GWT 650°	HF	CE	RoHS II	MADE IN ITALY
------	------	-------------	----	----	---------	---------------------

Estándares

EN 60670-1 EN 60670-22

Descripción

Caja de derivación con paredes lisas y tapa alta transparente. Fabricada en tecnopolímero antichoque a base de ABS resistente a los rayos UV y libre de halógenos. Tapa de policarbonato transparente ahumado. Grado de resistencia al impacto IK08. Resistencia al calor anormal hasta 650°C (GWT). Fijación de la tapa con tornillos de acero inoxidable. Par de apriete de los tornillos 0,8 Nm. Junta interna de goma blanda de alta adherencia. Posibilidad de doble aislamiento con tapones opcionales. Fijaciones internas para carriles DIN, regletas de conexiones o placa de fondo. Fabricada de conformidad con las normas EN 60670-1:2005 y EN 60670-22:2006. Temperaturas durante la instalación: mínima -5°C, máxima +60°C. Temperaturas de funcionamiento: mínima -25°C, máxima +70°C. Grado de protección IP56.

Dimensiones: 150x110x140 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)


CLASS EC002600 - Box/housing for surface mounting on the wall/ceiling

Rated insulation voltage Ui	400 V	Mounting method	Wall-/ceiling mounting	Degree of protection (IP)	IP56
Material	Plastic	Halogen free	Sí	Surface protection	Untreated
Colour	Grey	Width	150 mm	Depth	140 mm
Model	Junction box	Length	140 mm	Diameter	0 mm
Working temperature	-25-70 °C	Explosion-tested version	No	For Ex-zone gas	None
For Ex-zone dust	None	Cover model	Blind cover	Circuit integrity	None
Equipped with	None	Shape	Rectangular	Number of inlets	0
Inlet from the rear	No	Transparent cover	Sí	Connectable	No
Mounting in the soil	No	Mounting under water	No	Type of housing feed-through	None
Cover attachment	Screwed	Castable	Sí	Casting compound included	No
Sealable	No	With screening	No	Weatherproof	Sí

Documentation available for download



Dimensions and technical drawings



Barcode



8032636761613

Unit

1 NR

0.3333 [kg]



8059307213837

Cardboard

18 NR

0.605x0.4x0.35 [m]

5.9994 [kg]