EC60018BE

WALL-MOUNT MOD. ENCL. IP40 400X265X130 18M WHITE (T.B. 1x12)

Envolvientes > Montaje en pared > Armarios modulares > Serie 600 - ip40 con puerta transparente > Cuadro de distribución pequeño > Blanco - con bornera

Technical Symbols/Marks/Approvals

IP40 | GWT 650° | RoHS II | MADE IN ITALY

Estándares

EN 60670-1 EN 60670-24

Descripción

Cuadro de distribución de superficie. Fabricado en tecnopolímero antichoque a base de ABS resistente a los rayos UV y libre de halógenos. Grado de resistencia al impacto IK08. Resistencia al calor anormal hasta 650°C (GWT). Fondo y tapa en tecnopolímero libre de halógenos a base de ABS. Tapa reversible. Puerta de policarbonato ahumado. Etiqueta autoadhesiva de identificación de circuitos incluida. Tapón de cubierta para módulos no utilizados incluido. Tapones cubretornillos de fijación suministrados para mantener el grado de protección IP y el doble aislamiento. Carril DIN de acero galvanizado montado. Ajustable en dos alturas. Fabricado de conformidad con las normas EN 60670-1:2005 y EN 60670-22:2013. Temperaturas durante la instalación: mínima -5°C, máxima +60°C. Temperaturas de funcionamiento: mínima -25°C, máxima +70°C. Grado de protección IP40.
Dimensiones externas: 400x265x130 mm
18 módulos DIN
2 regletas de conexiones de 6x10 mm - 12 bornes
Potencia disipable: 30 W

Etim

GROUP EG000023 - Distribution boards

CLASS EC000214 - Small distribution board

Mounting method	Surface mounted	**Degree of protection (IP)**	IP40	**Width in number of modular spacings**	18
Colour	White	**Width**	400 mm	**Height**	265 mm
Depth	130 mm	**RAL-number**	9001	**UV resistant**	Sí
Type of covering	Door	**Type of door**	Single	**Transparent cover/door**	Sí
With lock	No	**Inner depth**	130 mm	**Number of rows**	1
Extension possible	No	**Housing material**	Plastic	**With mounting plate**	No
Signal passing door	No	**Type of closure**	Other	**Earthing terminal block**	Sí
Neutral terminal block	Sí	**DIN-rail**	Sí	**EMC-version**	No

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Technical Characteristics

Dimensiones	400x262x130 mm	**Equipo de montaje**	1	**Bloques de terminales/orificios**	2x12
Disipación de potencia (vatios) EN 60670-24	30 W	**Tipo_Morsettiera**	2x16 + 10x10 mm²		

Documentation available for download

Instruction booklet

Istruzioni 600-610_0423.pdf

Dimensions and technical drawings

EC60018_2025.pdf

Barcode

8053676578474

Unit

1 NR

2.166 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.