

ECICTA20N-UV

TUBO CORR. ICTA PP HF UV 34223 Ø20 mm - 100 m - NEGRO



Tuberías y accesorios > Tubería > Tubos corrugados (mangueras) > Serie icta - pp - 34223 - 750 n - uv > Tubo plástico para instalación eléctrica > Negro

Technical Symbols/Marks/Approvals



Estándares

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642


Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

| | | | | | |
|--|----------------------------|---|---------------------------|-----------------------------------|--------------------------|
| Flush-mounted installation | Sí | Material | Polypropylene (PP) | Halogen free | Sí |
| Colour | Black | RAL-number | 9005 | UV resistant | Sí |
| Suitable for underground installation | No | Operating temperature | -5-90 °C | Bending strength | Pliable, self recovering |
| Compressive strength class according to EN 61386-1 | Medium (class 3 / 2 Joule) | Impact strength class according to EN 61386-1 | Heavy (class 4 / 6 Joule) | With sleeve | No |
| Fire retardant version | Sí | Surface mounting | Sí | Suitable for installation on wood | Sí |
| Suitable for hollow wall installation | Sí | Suitable for concrete installation | Sí | Machine and systems installation | No |
| Suitable for underfloor installation (screed) | Sí | Suitable for outdoor installation | Sí | Inner diameter | 13.5 mm |
| Outer diameter | 20 mm | High conducting inner coating | Sí | With metre indication | No |

Barcode



8055035965543

Cardboard

100 MT

0.51x0.51x0.24 [m]

6.5 [kg]



8055035965550

Pallet

5000 MT

0.8x1.2x2.5 [m]

325 [kg]