

ECICTA50N-UV

TUBO CORR. ICTA PP HF UV 34223 Ø50 mm - 25 m - NEGRO



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Tuberías y accesorios > Tubería > Tubos corrugados
(mangueras) > Serie icta - pp - 34223 - 750 n - uv > Tubo
plástico para instalación eléctrica > Negro

Technical Symbols/Marks/Approvals

HF



GWT
850°

+90°



RoHS II

MADE
IN
ITALY

Estándares

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Sí	Material	Polypropylene (PP)	Halogen free	Sí
Colour	Black	RAL-number	9005	UV resistant	Sí
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Sí	Surface mounting	Sí	Suitable for installation on wood	Sí
Suitable for hollow wall installation	Sí	Suitable for concrete installation	Sí	Machine and systems installation	No
Suitable for underfloor installation (screed)	Sí	Suitable for outdoor installation	Sí	Inner diameter	38 mm
Outer diameter	50 mm	High conducting inner coating	Sí	With metre indication	No

Barcode



8055035965031

Cardboard

25 MT

4.87 [kg]



8055035965048

Pallet

800 MT

155.84 [kg]