EC625004

GRP POLYESTER ENCLOSURE SOLID DOOR 72 MODULES (4X18) 435X655X215 mm

Envolvientes > Montaje en pared > Cuadros de poliÉster reforzado con fibra de vidrio > Armarios > Armario de distribución (vacío) > Puerta ciega

Technical Symbols/Marks/Approvals

IP66 | GWT 960° | UL94 V0 | UV | IK10 | HF | CE | RoHS II | MADE IN ITALY

Estándares

EN 62208

Descripción

Cuadro de distribución de superficie. Fabricado en poliéster termoestable reforzado con fibra de vidrio. Libre de halógenos. Autoextinguible V0 según UL-94. Resistente a los rayos UV. Grado de resistencia al impacto IK10. Resistencia al calor anormal hasta 960°C (GWT). Temperaturas durante la instalación: mínima -25°C, máxima +60°C.
Tensión nominal de utilización 1000 VAC, 1500 VDC, apto para uso en instalaciones fotovoltaicas. Doble aislamiento. Posibilidad de instalar interruptores con alturas de 48-75-102 mm con carriles DIN ajustables en altura. Puerta reversible con apertura de más de 180° con pernos metálicos de acero inoxidable. Posibilidad de instalar cerradura de seguridad de cilindro. Tapón de cubierta para módulos no utilizados incluido. Tapones cubretornillos de fijación suministrados para mantener el grado de protección IP y el doble aislamiento. Fabricado de conformidad con las normas EN 62208:2011, EN 60695-2-11:2000/2001, IEC60754-1:2001/AMD1:2019, IEC60754-2:2011/AMD1:2019 e IEC60754-3:2018. Grado de protección IP66.
Dimensiones externas: 435x625x215 mm
72 módulos (4x18) paso 150 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000011 - Enclosures/cabinets

CLASS EC000261 - Enclosure/cabinet (empty)

Degree of protection (IP)	IP66	**Material**	Other	**Material quality**	GRP (Glass fibre reinforced plastic)
Surface finishing	Untreated	**Colour**	Grey	**Impact strength**	IK10
Width	435 mm	**Height**	655 mm	**Depth**	215 mm
With cover	Sí	**RAL-number**	7035	**With mounting plate**	No
Pre-stamping	No	**EMC-version**	No	**Suitable for wall mounting**	Sí
Couplable	Sí	**Mounting plate depth-adjustable**	Sí	**Suitable for wall built-in**	No
Pole fastening	Sí	**With door**	Sí	**Number of doors**	1
With glazed door	No	**With ventilation door**	No	**With rear door**	No
Number of locks	2	**Transparent cover**	No	**Suitable for outdoor set-up**	Sí
Pitched roof	No	**Number of connector holes**	0	**Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890**	56 W
Max. permitted load of the mounting plate according to IEC 62208	50 kg				

Documentation available for download

Instruction booklet

Istruzioni_625_0423.pdf

Certification

MI22-0079305-01a - ELETTROCANALI SPA - HCl_1 - TR_625.pdf

Certification

MI22-0079305-01b - ELETTROCANALI SPA - pH - TR_625.pdf

Certification

MI22-0079305-01c - ELETTROCANALI SPA - HCl_3 - TR_625.pdf

Certification

MI22-0079343-01_TR_625.pdf

Certification

Serie 625 IMQ_CA02.06897_2024.pdf

Brochure

Quadri Poliestere IT.pdf

Brochure

Quadri Poliestere_ENG.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8053676570379

Unit

1 NR

7.2 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.