

EC680M4

BRASS TERMINAL BLOCKS 5 HOLES

Envolventes > Accesorios > Accesorios > Borneras > Regletas de conexión en barra > Borneras de latón



Technical Symbols/Marks/Approvals



RoHS II

MADE
IN
ITALY

Estándares

EN 60670-1 EN 60670-24

Descripción

Regleta de bornes unipolar de latón de 5 vías. Material utilizado: latón UNI EN 12167 CW 614N. Tensión nominal 400VCA. Corriente nominal 125A. Suministrada completa con tornillos de acero con tratamiento anticorrosión de huella combinada o ranurada.

Sección 10x15 mm - Longitud 48,5 mm.

1 vía x 25 mm² - 4 vías x 10 mm².

Etim

GROUP EG000015 - Energy distribution systems

CLASS EC000275 - Main line branch terminal

Number of poles	1	Mounting method	Screw	Width	48.5 mm
Height	15 mm	Depth	10 mm	Connection type	Screwing
Nominal current	100 A	Number of inputs	1	Number of outputs	4
Suitable for solid conductors	Sí	Suitable for stranded conductors	Sí	Conductor cross section, input	25-25 mm ²
Conductor cross section, output	10-10 mm ²	Contact safe	No		

Dimensions and technical drawings



EC680M4.2026.pdf

Barcode



8050880882847

Cardboard

10 NR

0.6 [kg]