

EC74320

BEND 90° IP67 Ø20 mm - GREY - SECURITY

Tuberías y accesorios > Accesorios de tubería > Uniones y sistemas de fijaciÓn > Security system - acesorios ip67 > codo para tubos de instalación

Technical Symbols/Marks/Approvals

IP67 | HF | GWT 850° | IK07 | CE | RoHS II | MADE IN ITALY

Estándares

EN 61386-1 EN 61386-21

Descripción

Curva a 90° para la conexión entre dos tubos de idéntico diámetro fabricada en tecnopolímeros resistentes a los impactos coextruidos de baja emisión de humos. Grado de protección IP67. Grado de autoextinguibilidad V2 según la norma UL94. Resistencia al calor anormal (GWT IEC 60695-2-11): hasta 850 °C. Fabricada de conformidad con las normas EN 61386-1, EN 61386-21.
Diámetro 20 mm - Radio de curvatura 100 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyethylene (PE)	**Halogen free**	Sí
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	20 mm	**Flexible**	No	**UV resistant**	Sí
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	20 mm
With sleeve	Sí	**Two-part**	No	**With inspection opening and cover**	No
Radius	100 mm	**Bend angle**	90 °		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Raccordi Security System_2023.pdf

Barcode

8050880883998

Pack

10 NR

0.228 [kg]

8057711591688

Cardboard

100 NR

0.295x0.39x0.21 [m]

2.28 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.