

EC75516

FLEXIBLE BEND PIPE-BOX IP65 Ø16 mm - GREY - SPEED SYSTEM

Tuberías y accesorios > Accesorios de tubería > Uniones y sistemas de fijaciÓn > Speed system - acesorios ip65 > codo para tubos de instalación > Curva flexible ip65 (caja de conductos)

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Estándares

EN 61386-1 EN 61386-21

Descripción

Curva flexible para la conexión entre un tubo y una caja de derivación fabricada en tecnopolímero resistente a los impactos a base de PVC rígido. Anillo interno blando de estanqueidad para la compensación de las tolerancias de los tubos. Grado de protección IP65. Grado de autoextinguibilidad V0 según la norma UL94. Resistencia al calor anormal (GWT IEC 60695-2-11): hasta 960 °C. Producida de conformidad con las normas EN 61386-1, EN 61386-21.
Diámetro 16 mm - longitud 200 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	16 mm	**Flexible**	Sí	**UV resistant**	Sí
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	16 mm
With sleeve	Sí	**Two-part**	No	**With inspection opening and cover**	No
Radius	160 mm	**Bend angle**	90 °		

Technical Characteristics

largura	200 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050507872411

Pack

50 NR

1.625 [kg]



8050507872428

Cardboard

200 NR

0.605x0.4x0.26 [m]

6.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.