

EC9008060

TRUNKING WITH COVER FOR AIR-CONDITIONED INSTALLATION DIM. 80X60

Canalizaciones > ClimatizaciÓn > Canales para aire acondicionado > Canales > Canal para aire acondicionado

Technical Symbols/Marks/Approvals

IP40 | UL94 V0 | GWT 960° | UV | CE | RoHS II | MADE IN ITALY

Descripción

Canaleta para sistemas de aire acondicionado fabricada en tecnopolímero a base de PVC rígido autoextinguible y resistente a los rayos UV. Perforación previa del fondo para fijación con tornillos y tacos. Predispuesta para el enganche de bridas de cableado. Tapa envolvente suministrada.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC001938 - Wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Polyvinyl chloride (PVC)
Halogen free	No	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK07	**Width**	80 mm
Depth	60 mm	**Length**	2000 mm	**Usable cross section**	3910 mm²
RAL-number	9001	**Mounting method cover**	Spanned	**With protective foil**	No
Working temperature	-25 ÷ 70 °C	**Number of plug-in partitions**	0	**With cable fixing clip**	No
With duct connector	No	**Bottom perforation**	No	**Number of covers**	1
Cover width 1	80 mm	**Cover width 2**	0 mm	**Cover width 3**	0 mm
Symmetric	Sí	**Covers included**	Sí	**Construction type rectangular**	Sí
Construction rear wall (inner side)	Perforated				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050880884834

Cardboard

16 MT

0.248x0.143x2.03 [m]

12 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.