

ECS2580B



SLOTTED TRUNKING WITH COVER S 4/6/4 DIM. 25X80 WHITE

Goulottes > Systèmes de tableaux de distribution > Systèmes de câblage > Goulottes > Goulotte de câblage > Blanc - type s
- lamelles Étroites 4/6/4




IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Symboles/marques/approbations techniques



Normes

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Goulottes de câblage

CLASS EC000012 - Goulotte de câblage

Matériau	PVC	Sans halogène	No	Couleur	Blanc
Type de fixation	Perforation du fond	Largeur	25 mm	Hauteur	80 mm
Longueur	2 m	Distance entre les fentes	6 mm	Largeur de fente	4 mm
Finition de paroi latérale	Poinçonnage à trous/fentes	Auto-extinguible	Oui	Flexible	No
Section transversale utile	1520 mm²	Avec partie supérieure	Oui	Numéro RAL	9001

Caractéristiques techniques

Prédisposition du séparateur NO

Documentation disponible en téléchargement



Certification

Certificato UL A-S
ATL AMF
E331386.pdf



Certification

RINA
DCMTVL_1005538
_380865962_2025.
PDF



Certification

Canali asolati tipo S
IMQ_EI617_2020.p
df

Code à barres



8059307211680

Cardboard

56 MT

0.26x0.18x2.027 [m]

24.0016 [kg]



8055035960265

Pallet

1008 MT

1.2x0.8x2.2 [m]

432.0288 [kg]