

TECHNICAL DATA SHEET

MAIN CHARACTERISTICS

SKIRTING BOARD AND FRAME MAXISYSTEM - SIMPLYSYSTEM SERIES

CONSTRUCTIVE TECHNICAL CHARACTERISTICS

Trunking skirting board and frame with 3 or 5 compartments and accessories.
External dimensions: 70x20 and 130x28 mm.
Perforated bottom 4x8 mm for an easier installation.
Material: made of technopolymer on rigid PVC base, self-extinguishing V0 degree to UL94 and high resistance to UV rays.
Standard colours: white RAL 9001 and slate RAL 7021.
IP40 Protection degree.
Shock resistance: IK08 (up to 6 J).
Resistance to heat in continuous use up to 70°C.
Resistance to abnormal heat: up to 650°C (Glow Wire Test according to IEC 60695-2-11 standard).
Insulation resistance > 100 MΩ.
Dielectric voltage 4,5 Kv/mm.
Application temperature: minimum -5°C, maximum +60°C.
Standard length: 2 mt bars.
Made in compliance with EN 50085-1:2005 +A1:2013, EN 50085-2-1:2006 +A1:2011 standards.
Approvals: IMQ.
Products in compliance with RoHS II - 2011/65/EU directive + 2015/863/EU.
Products meeting the safety objectives of Low Voltage Directive 2014/35/EU (Annex I).
Made in Italy.



ELETTROCANALI S.p.a.

Quality Manager
Valsecchi Luca