
elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECA4040BL

SLOTTED TRUNKING WITH COVER A 8/12/8 DIM. 40X40 BLUE

Trunkings > Panelboards systems > Cable management > Slotted trunkings > Slotted cable trunking > Blue - type a - wide slots 8/12/8

Technical Symbols/Marks/Approvals

UL94 V0 | GWT 960° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	**Halogen free**	No	**Colour**	Blue
Type of fastening	Bottom perforation	**Width**	40 mm	**Height**	40 mm
Length	2000 mm	**Diameter**	0 mm	**Distance of slots**	12 mm
Slit width	8 mm	**Type of side wall**	Hole-/slot punching	**Self-extinguishing**	Yes
Flexible	No	**Usable cross section**	1214 mm²	**With cover/lid**	Yes
RAL-number	5012				

Technical Characteristics

Separator predisposition	NO

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8056351666046
Cardboard
70 MT
0.26x0.18x2.027 [m]
23.99999 [kg]



8055035961019
Pallet
1260 MT
1.2x0.8x2.2 [m]
431.99982 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.