

ECCAP5012B

FLOOR CABLE TRUNKING WITH COVER mm 50X12 WHITE - 3 COMPARTMENTS



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Trunkings > Wall and ceiling > Solid cable trunkings > Series
cap - floor ducts > On-floor installation duct

Technical Symbols/Marks/Approvals

IP40	IK08	UL94 V0	GWT 960°	RoHS II	CE	MADE IN ITALY
------	------	------------	-------------	---------	----	---------------------

Norms

EN 50085-1 EN 50085-2-1

Description

Floor trunking made of self-extinguishing rigid PVC technopolymer. Impact resistance: 6J. Base designed for silicone adhesive fixing and perforated for screw and plug fixing. Wrap-around cover, removable only with tools. Trampling-resistant, load capacity 0.4 kg/cm².

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000722 - On-floor installation duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Other
Halogen free	No	Anti-bacterial treatment	No	Colour	White
Impact strength	IK07	Width	50 mm	Height	12 mm
Length	2 m	RAL-number	9001	Working temperature	-5-60 °C
Number of channels	3	With cover cap	No	Permitted cable diameter	6-10 mm
Bottom perforation	Yes	Slotted hole	Yes	With fixation	No
Demountable	Yes	Self-adhesive	No	Sealing lip	Yes
With anti-slip layer	No	Reflective	No	Fuel- and oil resistant	No
Resistance to vertical load applied in a small surface according IEC 61084-2-2	1000 N	Resistance to vertical load applied in a large surface according IEC 61084-2-2	7000 N	Suitable for car	No
Suitable for truck	No	Bending strength	Rigid		

Barcode



8050880886746

Cardboard

50 MT

0.195x0.102x2.025 [m]

13.5 [kg]