



FLOOR CABLE TRUNKING WITH COVER mm 75X17 GREY - 3 COMPARTMENTS



Trunkings > Wall and ceiling > Solid cable trunkings > Series cap - floor trunkings > Floor mount trunkings

Technical Symbols/Marks/Approvals

IP 40	IK 08	UL94 V0	GWT 960 °	RoHS II	C€	MADE IN ITALY	
--------------	--------------	-------------------	---------------------	---------	----	---------------------	--

Norms

EN 50085-1 EN 50085-2-1

Description

Floor trunking made of self-extinguishing rigid PVC technopolymer. Impact resistance: 6J. Base designed for silicone adhesive fixing and perforated for screw and plug fixing. Wrap-around cover, removable only with tools. Trampling-resistant, load capacity 0.4 kg/cm².

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000722 - On-floor installation duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Other
Halogen free	No	Anti-bacterial treatment	No	Colour	Grey
Impact strength	IK07	Width	75 mm	Height	17 mm
Length	2 m	RAL-number	7030	Working temperature	-5-60 °C
Number of channels	3	With cover cap	No	Permitted cable diameter	10-12 mm
Bottom perforation	Yes	Slotted hole	Yes	With fixation	No
Demountable	Yes	Self-adhesive	No	Sealing lip	Yes
With anti-slip layer	No	Reflective	No	Fuel- and oil resistant	No
Resistance to vertical load applied in a small surface according IEC 61084-2-2	1500 N	Resistance to vertical load applied in a large surface according IEC 61084-2-2	10000 N	Suitable for car	No
Suitable for truck	No	Bending strength	Rigid		





Barcode



8050880886760

Cardboard

50 MT

0.248x0.143x2.03 [m]

22 [kg]