elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECCV32

FLEXIBLE BEND 32 mm

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > Flexible bend

Technical Symbols/Marks/Approvals

IP64 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Flexible bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. IP64 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 32 mm - length 380 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	32 mm	**Flexible**	Yes	**UV resistant**	Yes
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	32 mm
With sleeve	Yes	**Two-part**	No	**With inspection opening and cover**	No
Radius	320 mm	**Bend angle**	90 °C		

Technical Characteristics

length	380 mm

ELETTROCANALI s.p.a. | Via Gen. C. A. dalla Chiesa, 18 - 24020 Scanzorosciate BG Italy | T. +39 035 665077 | info@elettrocanali.com

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880888290

Pack

10 NR

0.75 [kg]

8057711593620

Cardboard

80 NR

0.4x0.605x0.26 [m]

6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.