elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECGSU25

LONG JOINT IP40 Ø25 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint conduit - conduit > Long rigid conduit joints

Technical Symbols/Marks/Approvals

IP40 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | NF | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Coupling for the connection between two pipes of the same diameter, made of shockproof technopolymer based on rigid PVC. IP40 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 25 mm - Length 80 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
UV resistant	Yes	**Quality of surface coating**	Uncoated	**Surface polished**	No
Surface brushed	No	**Suitable for nominal tube diameter**	25 mm	**Two-part**	No
With inspection opening and cover	No	**With lock function**	No	**Material sealing**	No sealing
With outer thread	No	**With inner thread**	No	**Separable**	No
Eccentric	No				

Technical Characteristics

length	80 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Tubo Rigido TG15 e Raccordi_2023.pdf



Certification

LICENCE NF - TG15 -2022 - Licence - Certificat Produits-14694838-778138-0000732340-6.p....pdf

Barcode

8050880888856

Pack

50 NR

0.86 [kg]

8057711594122

Cardboard

500 NR

0.605x0.4x0.26 [m]

8.6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.