elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECGSU32H

HF LONG JOINT IP40 Ø32 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint conduit - conduit > Long rigid conduit joints

Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Coupling for the connection between two pipes of identical diameter, made of shockproof Halogen-Free ABS-based technopolymer. IP40 protection rating. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 650 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 32 mm - Length 100 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

Material	Plastic	**Material quality**	Other	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
UV resistant	Yes	**Quality of surface coating**	Uncoated	**Surface polished**	No
Surface brushed	No	**Suitable for nominal tube diameter**	32 mm	**Two-part**	No
With inspection opening and cover	No	**With lock function**	No	**Material sealing**	No sealing
With outer thread	No	**With inner thread**	No	**Separable**	No
Eccentric	No				

Technical Characteristics

length	100 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880888887

Pack

25 NR

0.6 [kg]

8057711594153

Cardboard

250 NR

0.605x0.4x0.26 [m]

6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.