

**ECICTA50KT**

**HF ICTA PLIABLE PP CONDUIT 34223 1000 N Ø50 mm - 25 m - BLUE - WITH DRAW TAPE**

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Yes	<b>Material</b>	Polypropylene (PP)	<b>Halogen free</b>	Yes
<b>Colour</b>	Blue	<b>RAL-number</b>	5005	<b>UV resistant</b>	No
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-5-90 °C	<b>Bending strength</b>	Pliable, self recovering
<b>Compressive strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>Impact strength class according to EN 61386-1</b>	Heavy (class 4 / 6 Joule)	<b>With sleeve</b>	No
<b>Fire retardant version</b>	Yes	<b>Surface mounting</b>	No	<b>Suitable for installation on wood</b>	Yes
<b>Suitable for hollow wall installation</b>	Yes	<b>Suitable for concrete installation</b>	Yes	<b>Machine and systems installation</b>	No
<b>Suitable for underfloor installation (screed)</b>	Yes	<b>Suitable for outdoor installation</b>	No	<b>Inner diameter</b>	38 mm
<b>Outer diameter</b>	50 mm	<b>High conducting inner coating</b>	Yes	<b>With metre indication</b>	No

**Documentation available for download**

**Certification**

**Test Report ICTA**  
Contenuto alogeni  
MI23-0092109-01.pdf

## Barcode



8054320281665

**Cardboard**

25 MT

7.82 [kg]



8054320281696

**Pallet**

800 MT

250.24 [kg]